

# C-Bus® 360 Degree Indoor PIR Movement Sensor

C-Bus®

**CLIPSAL**  
LIVING ELECTRICAL



5753L Series

The C-Bus® 360 Degree Indoor PIR Movement Sensor is a C-Bus® input unit used to detect movement by sensing the natural thermal radiation emitted from any moving body. When movement is detected, the unit issues commands over the C-Bus® network to control C-Bus® output devices. The sensor is suitable for controlling lighting in homes, apartments, offices, corridors, conference rooms etc.

The sensor incorporates the C-Bus® 'Learn Mode' feature. Learn mode allows the units to be programmed without the need for a PC to be connected to the system. Alternatively, the units can be programmed via a PC using the installation software.

The C-Bus® 360 Degree Indoor PIR Movement Sensor has a 360 degree field of view and minimum detection coverage of 5 metres when mounted 2.4 metres above the floor, noting that the coverage is slightly elliptical.

The unit is small and unobtrusive and is designed to be flush mounted. It is ideally suited for mounting to the ceiling or to suspend from ceiling tiles. The visible lens is approximately the size of a low voltage dichroic halogen lamp.

The sensor is capable of controlling up to four C-Bus® 'Group Addresses', with each being controlled for a different period if required.

An added feature is that each sensor includes an ambient light level sensor (Sunset Switch) feature, which automatically turns lights 'on' when the ambient light level falls below the threshold level (at sunset), and then turns the lights 'off' again at sunrise. Alternatively, the lights can be programmed to automatically turn 'off' at a set time after sunset.

A light emitting diode (LED) on the sensor head can be programmed to turn on when movement is detected. This enables easy positioning and commissioning of the sensor.

The unit initiates a regular status report, which compares the status of all input and output units within the same

C-Bus® 'Application Address'. If a state disagreement exists between the output units and the input units, the C-Bus® Indoor PIR Movement Sensor will change its internal state to suit the output.

[clipsal.com/cis](http://clipsal.com/cis)

**CLIPSAL**  
  
Control and Management System

## 5753L C-Bus® 360 Degrees Indoor PIR Movement Sensor

- Flush mount design ideal for mounting to the ceiling or ceiling tiles
- Ideally suited for mounting in the centre of cellular offices
- Discrete appearance – only 65mm diameter face is visible
- Low profile – only 8mm protrusion from the ceiling
- 50mm circular cut-out hole
- 240V ac connection is not required
- C-Bus® Learn Enabled
- 360 degree detection pattern
- Minimum 5m detection coverage when mounted 2.4m above the floor
- Capable of controlling up to four C-Bus® 'Group Addresses'
- An LED on the sensor can be programmed to turn on when movement is detected
- Light sensitivity is set via an adjustment screw located on the sensor unit
- Dual element detectors minimise false triggering
- Refer to 5753L Installation Instruction for location and mounting details
- Designed to meet Australian and European standards for EMC Compliance and Safety
- Configured via either the C-Bus® Installation Software or via the C-Bus® Learn Enabled feature
- Communication with other C-Bus® devices and the supply voltage is obtained via a single C-Bus® twisted pair cable
- An inbuilt non-volatile memory retains programmed information of the unit in the event of a power failure
- Initiates a regular status report, which compares the status of all input and output units within the same C-Bus® 'Application Address'
- A light emitting diode (LED) status indicator on the unit is used to report the current state of the load controlling device
- Dimensions – sensor housing,  
W = 65mm, L = 115mm  
Dimensions – locking ring,  
W = 96mm, H = 13mm
- Weight = 45g.

## Product of Clipsal Australia Pty. Ltd.

A member of the Schneider Electric Group.

### Head Office

12 Park Terrace, Bowden  
South Australia 5007  
PO Box 103 Hindmarsh  
South Australia 5007

Telephone +61 8 8345 9500  
Facsimile +61 8 8346 0845  
Internet www.clipsal.com/cis  
E-Mail cis@clipsal.com.au

**CIS Technical Support Hotline:**  
1300 722 247

**Customer Service Enquiries:**  
**1300 2025 25**

**National Customer Service Facsimile:**  
**1300 2025 56**

### International Enquiries

#### International Sales and Marketing

Telephone +61 8 8269 0587  
Facsimile +61 8 8340 7350  
E-Mail export@clipsal.com.au

#### New Zealand

Clipsal Industries (NZ) Ltd  
Telephone +64 9 576 3403

#### Malaysia

Clipsal Integrated Systems (M) Sdn Bhd  
Telephone +60 3 7665 3555

#### Singapore

Clipsal Integrated Systems Pte Ltd  
Telephone +65 6415 3232/3233

#### China

Clipsal China Limited  
Telephone +86 755 8237 5959

#### Greece

Schneider Electric AE  
Telephone +30 69 4646 3200

#### Hong Kong

Clipsal Integrated Systems (HK) Limited  
Telephone +852 2487 0261

#### India

Schneider Electric India Pvt Ltd  
Telephone +91 11 5159 0000

#### Indonesia

PT Clipsal Graha Nusa  
Telephone +62 21 630 6430

#### Korea

Clipsal Korea Co. Ltd  
Telephone +82 549 5550

#### Pakistan

Clipsal Pakistan (Pvt) Ltd  
Telephone +92 21 506 7278

#### Philippines

Clipsal Philippines Inc.  
Telephone +632 683 0275-78

#### South Africa

Clipsal South Africa (Pty) Ltd  
Telephone +27 11 314 5200

#### Taiwan

Clipsal (Taiwan) Co Ltd  
Telephone +886 2 2558 3456

#### Thailand

Clipsal Thailand Ltd  
Telephone +66 2 952 5338-42

#### United Arab Emirates

Clipsal Middle East  
Telephone +971 6 5570 777

#### United Kingdom

Clipsal Integrated Systems  
C/o Schneider Electric  
Telephone +44 870 608 8 608

#### Vietnam

Clipsal - VTEC  
Telephone +848 856 3002



Clipsal Australia Pty Ltd reserves the right to change specifications, modify designs and discontinue items without incurring obligation and whilst every effort is made to ensure that descriptions, specifications and other information in this catalogue are correct, no warranty is given in respect thereof and the company shall not be liable for any error therein.

© Clipsal Australia Pty Ltd.

The identified trademarks and copyrights are the property of Clipsal Australia Pty Ltd unless otherwise noted.