

# C-Bus® 2-Channel DALI Interface DIN Rail Series

C-Bus®

**CLIPSAL**  
LIVING ELECTRICAL



5502DAL

The 5502DAL C-Bus® DALI Interface unit is a C-Bus® system support device designed to provide an isolated communications path between a C-Bus® Network and two DALI Networks. For ease of installation the unit is DIN rail mounted, measuring 4M wide (1M = 17.5 +0.5/-0.0 mm).

The DALI Interface provides two-way communication, i.e. selected C-Bus® messages are routed to an appropriate DALI Network, and DALI lighting messages are routed to the C-Bus® Network.

The DALI Interface constantly monitors both DALI Networks. It is capable of detecting and reporting faulty lamps in fluorescent ballasts or failed DALI units to C-Bus®.

Each DALI Network can have up to 64 addressable DALI devices, such as fluorescent ballasts and low voltage transformers. The DALI Interface does not have its own DALI addresses, i.e. it is transparent and is not "visible" for other DALI devices.

The DALI Interface product incorporates a C-Bus® PC Interface Module for communications to the C-Bus® Network. Programming of the C-Bus® side of the Network Interface can be done in the same manner as programming a standard PC Interface.

[clipsal.com/cis](http://clipsal.com/cis)

## 5502DAL C-Bus® DALI Interface Module

- Provides an isolated communications path between a C-Bus® Network and two DALI Networks
- DIN rail mounted, measuring 4M wide (1M = 17.5 +0.5/-0.0 mm)
- Provides two-way communication, i.e. selected C-Bus® messages are routed to an appropriate DALI Network, and DALI lightning messages are routed to the C-Bus® Network
- Constantly monitors both DALI Networks
- Capable of detecting and reporting to C-Bus® faulty lamps in fluorescent ballasts or failed DALI units
- Incorporates a C-Bus® PC Interface Module for communications to the C-Bus® Network
- Programming of the C-Bus® side of the Network Interface can be done in the same manner as programming a standard PC Interface
- In normal operation, the unit draws 32mA from the C-Bus® Network
- Contains a pre-programmed C-Bus® to DALI and DALI to C-Bus® addressing structure
- Consumes 32mA from the C-Bus® network during normal operation
- C-Bus® connections via 2 x RJ45 connectors, allowing similar units to be quickly looped together
- Capable of generating a C-Bus® clock signal and providing a C-Bus network burden. Selectable through the C-Bus® Installation software
- Incorporates a C-Bus® and Unit indicator, showing the status of the C-Bus® Network and the status of the individual unit
- Incorporates an onboard non-volatile memory, which is used to store the operating state of the unit in the case of a power loss
- Capable of being programmed via the installation software without the need for a mains connection
- A maximum of 50 units may be connected to a single C-Bus® network
- Configured via the C-Bus® Installation Software or the Learn Enabled Features
- Supplied with a 300mm C-Bus® Category 5 patch lead complete with pre-terminated RJ45 connectors
- The output terminals accommodate 2 x 1.5mm<sup>2</sup> or 1 x 2.5mm<sup>2</sup> cable
- EMC Compliant to meet the requirements for marking with the CE and C-Tick marks
- Dimensions: W=72mm, H=85mm, D=65mm
- Weight: 130g.

*Note: Clipsal Integrated Systems does not manufacture DALI units, power supplies, commissioning software or any other product or service associated with DALI aside from the DALI Interface itself.*

*Check individual DALI component requirements.*

### Product of Clipsal Australia Pty. Ltd.

A member of the Schneider Electric Group.

#### Head Office

12 Park Terrace, Bowden  
South Australia 5007  
PO Box 103 Hindmarsh  
South Australia 5007

Telephone +61 8 8345 9500  
Facsimile +61 8 8346 0845  
Internet www.clipsal.com/cis  
E-Mail cis@clipsal.com.au

#### CIS Technical Support Hotline:

1300 722 247

#### Customer Service Enquiries:

**1300 2025 25**

#### National Customer Service Facsimile:

**1300 2025 56**

#### International Enquiries

##### International Sales and Marketing

Telephone +61 8 8269 0587  
Facsimile +61 8 8340 7350  
E-Mail export@clipsal.com.au

##### New Zealand

Clipsal Industries (NZ) Ltd  
Telephone +64 9 576 3403

##### Malaysia

Clipsal Integrated Systems (M) Sdn Bhd  
Telephone +60 3 7665 3555

##### Singapore

Clipsal Integrated Systems Pte Ltd  
Telephone +65 6415 3232/3233

##### China

Clipsal China Limited  
Telephone +86 755 8237 5959

##### Greece

Schneider Electric AE  
Telephone +30 69 4646 3200

##### Hong Kong

Clipsal Integrated Systems (HK) Limited  
Telephone +852 2487 0261

##### India

Schneider Electric India Pvt Ltd  
Telephone +91 11 5159 0000

##### Indonesia

PT Clipsal Graha Nusa  
Telephone +62 21 630 6430

##### Korea

Clipsal Korea Co. Ltd  
Telephone +82 549 5550

##### Pakistan

Clipsal Pakistan (Pvt) Ltd  
Telephone +92 21 506 7278

##### Philippines

Clipsal Philippines Inc.  
Telephone +632 683 0275-78

##### South Africa

Clipsal South Africa (Pty) Ltd  
Telephone +27 11 314 5200

##### Taiwan

Clipsal (Taiwan) Co Ltd  
Telephone +886 2 2558 3456

##### Thailand

Clipsal Thailand Ltd  
Telephone +66 2 952 5338-42

##### United Arab Emirates

Clipsal Middle East  
Telephone +971 6 5570 777

##### United Kingdom

Clipsal Integrated Systems  
C/o Schneider Electric  
Telephone +44 870 608 8 608

##### Vietnam

Clipsal - VTEC  
Telephone +848 856 3002



Clipsal Australia Pty Ltd reserves the right to change specifications, modify designs and discontinue items without incurring obligation and whilst every effort is made to ensure that descriptions, specifications and other information in this catalogue are correct, no warranty is given in respect thereof and the company shall not be liable for any error therein.

© Clipsal Australia Pty Ltd.

The identified trademarks and copyrights are the property of Clipsal Australia Pty Ltd unless otherwise noted.