


C-Bus® 4 Channel Relay, DIN Rail Series



L5504RVF Series

The L5504RVF Series units are C-Bus® relay switching devices designed to be mounted in electrical switchboards or similar enclosures. For ease of installation, they are DIN rail mounted, measuring 8 DIN modules wide. Four independent voltage free relay contacts are provided for general switching applications.

The units include all C-Bus® Learning features, which allow the units to be programmed without the need for a PC connected to the system. Alternatively, units can be programmed via a PC and the C-Bus® installation software. The series includes units complete with 10A rated relays for resistive, inductive or fluorescent loads.

The units consume no current from the C-Bus® network during normal operation. The series includes units available both with and without a 200mA C-Bus® power supply for powering other C-Bus® devices connected to the network (eg. C-Bus® Wall Switches, Touchscreens, PIR detectors, etc).

C-Bus® connections are conveniently achieved at the unit through the use of RJ45 connectors, allowing similar units to be quickly looped together.

This series of C-Bus® units is capable of generating a C-Bus® clock signal and providing a C-Bus network burden. Both the clock signal and the burden are selectable through the C-Bus® Installation software.

Local toggle buttons are included to allow individual channels to be toggled at each unit, as well as via C-Bus® commands. Remote ON and OFF facilities are available, permitting all channels to be turned ON or OFF without C-Bus® network communication.

The unit optically isolates the mains power from the safe extra low voltage C-Bus® network.

LED Indicators are provided to show the status of the C-Bus® Network and the status of the unit.

clipsal.com/cis

L5504RVF Series C-Bus® Relay Modules

- Provides four independent voltage free relay contacts in an 8M wide DIN rail enclosure
- Units available with 10A rated relays (resistive, inductive or fluorescent loads) and separate units with relays rated at 10A resistive and 1A fluorescent
- Units available both with and without a 200mA C-Bus® power supply on-board
- Up to 100 units without power supply or 10 units with power supply are permitted on any one single C-Bus® network (255 networks available in a C-Bus® installation)
- Configured via either the C-Bus® Installation Software or via the Learn Enabled Features
- Local ON/OFF toggle buttons allow individual channels to be manually overridden at each unit
- Remote ON and OFF facilities permit all channels to be turned ON or OFF without C-Bus® network communication
- The C-Bus® side and output stages are electrically isolated
- Incorporates C-Bus® Network Status, Mains Power Status, and Load Status indicators
- Capable of generating a C-Bus® clock signal if enabled
- A network burden is incorporated and is software selectable
- Logic states (and / or) configurable via installation software
- Relay interlocking feature selectable via installation software
- Incorporates power recovery options to restore loads 'as was', 'off' or 'on'
- 2 x RJ45 sockets are incorporated to facilitate the C-Bus® connection
- Supplied with a 300mm C-Bus® Category 5 patch lead complete with pre-terminated RJ45 connectors
- The output terminals accommodate 2 x 1.5mm² or 1 x 4.0mm² cable
- EMC Compliant to meet the requirements for marking with the CE and RCM marks
- Incorporate magnetically latching relays
- Capable of being programmed via the installation software without the need for a mains connection
- Draws 18mA when being programmed and no mains connection is made
- When a mains connection is made, then the unit does not draw any current from C-Bus®
- Dimensions: W=144mm, H=85mm, D=65mm
- Weight: 375g.

Product of Clipsal Australia Pty. Ltd.

A member of the Schneider Electric Group.

Head Office

12 Park Terrace, Bowden
South Australia 5007
PO Box 103 Hindmarsh
South Australia 5007

Telephone +61 8 8345 9500
Facsimile +61 8 8346 0845
Internet www.clipsal.com/cis
E-Mail cis@clipsal.com.au

CIS Technical Support Hotline:
1300 722 247

Customer Service Enquiries:
1300 2025 25

National Customer Service Facsimile:
1300 2025 56

International Enquiries

International Sales and Marketing

Telephone +61 8 8269 0587
Facsimile +61 8 8340 7350
E-Mail export@clipsal.com.au

New Zealand

Clipsal Industries (NZ) Ltd
Telephone +64 9 576 3403

Malaysia

Clipsal Integrated Systems (M) Sdn Bhd
Telephone +60 3 7665 3555

Singapore

Clipsal Integrated Systems Pte Ltd
Telephone +65 6415 3232/3233

China

Clipsal China Limited
Telephone +86 755 8237 5959

Greece

Schneider Electric AE
Telephone +30 69 4646 3200

Hong Kong

Clipsal Integrated Systems (HK) Limited
Telephone +852 2487 0261

India

Schneider Electric India Pvt Ltd
Telephone +91 11 5159 0000

Indonesia

PT Clipsal Graha Nusa
Telephone +62 21 630 6430

Korea

Clipsal Korea Co. Ltd
Telephone +82 549 5550

Pakistan

Clipsal Pakistan (Pvt) Ltd
Telephone +92 21 506 7278

Philippines

Clipsal Philippines Inc.
Telephone +632 683 0275-78

South Africa

Clipsal South Africa (Pty) Ltd
Telephone +27 11 314 5200

Taiwan

Clipsal (Taiwan) Co Ltd
Telephone +886 2 2558 3456

Thailand

Clipsal Thailand Ltd
Telephone +66 2 952 5338-42

United Arab Emirates

Clipsal Middle East
Telephone +971 6 5570 777

United Kingdom

Clipsal Integrated Systems
C/o Schneider Electric
Telephone +44 870 608 8 608

Vietnam

Clipsal - VTEC
Telephone +848 856 3002



Clipsal Australia Pty Ltd reserves the right to change specifications, modify designs and discontinue items without incurring obligation and whilst every effort is made to ensure that descriptions, specifications and other information in this catalogue are correct, no warranty is given in respect thereof and the company shall not be liable for any error therein.

© Clipsal Australia Pty Ltd.

The identified trademarks and copyrights are the property of Clipsal Australia Pty Ltd unless otherwise noted.