

## Motion detector

# IS 3360

EAN 4007841033538



### Functional description

Large spaces, multi-storey car parks and production buildings with ceiling heights of up to 4 m rarely provide installation surfaces every metre. These environments call for motion detectors with a long reach. Like the IS 3360. It detects any tangential movement within an all-round radius of 20 metres. Even installed at heights of up to 4 metres. In short: one IS 3360 covers an area of more than 1000 m<sup>2</sup>! STEINEL Infrared technology that keeps its promises.

### Technical specifications

<b>Dimensions</b>	65 x Ø 126 mm
<b>Model</b>	Movement sensor
<b>Sensor type</b>	Passive infrared
<b>Power supply</b>	KNX bus voltage
<b>Recommended installation height</b>	2.5-4 m
<b>Installation</b>	Ceiling
<b>Reach, tangential</b>	20 m
<b>Detection angle</b>	360° with 180° angle of aperture
<b>Twilight setting</b>	2 - 1000 Lux
<b>Light output</b>	2 channels, including dimming level and basic light level
<b>Presence output</b>	Switching response irrespective of light level
<b>HVAC output</b>	Switching response irrespective of light level
<b>Photo-cell controller output</b>	Switching response governed by light level
<b>Further outputs</b>	Light level, sabotage protection
<b>Time setting</b>	1-255
<b>IP rating</b>	IP54
<b>Temperature range</b>	-20-+50
<b>Version</b>	KNX – Surface-mounted, round
<b>Model</b>	KNX

Motion detector

# IS 3360

EAN 4007841033538

## Sensorenerfassungsbereich 1

