



Power and productivity  
for a better world™



---

### Radio Time Switch, 8-channel, MDRC

---

Article no. FW/S8.2.1

---

Description

- » 8 channels
- » 800 switching times
- » 15 weekly programs
- » Daily, weekly and yearly program
- » 16 special programs including Continuous ON / continuous OFF available via object
- » 2 random programs
- » Astronomical switching program
- » ON-OFF switching times, pulse program, cycle program
- » Automatic changeover summer/winter time
- » Text-based operator guidance

---

Technical data

- » Operating voltage KNX: Bus voltage,  $\leq 10$  mA
- » Operating voltage: 110–240 V AC
- » Frequency: 50 - 60 Hz
- » Power consumption: typ. 1 W
- » Standby output: min. 0.8 W
- » Width: 3 module
- » Connection type: KNX bus terminal
- » Max. cable cross-section: 2.5 mm<sup>2</sup>
- » Installation type: DIN-rail
- » Number of channels: 8
- » Number of memory locations: 800
- » Time accuracy:  $\leq \pm 0.5$  s/day(Quartz) or DCF77/GPS
- » Shortest switching time: 1 s
- » Display: LCD
- » Ambient temperature: -5 °C ... +45 °C
- » IP rating: IP 20
- » Protection class: II in accordance with EN 60 730-1

---